



***This Confirmation of Product Type Approval is valid only as of 11/DEC/2008
for the below listed product.***

Please refer to the "Service Restrictions" shown below to determine if Unit Certification is required for this product.

This is to certify that, pursuant to the Rules of American Bureau of Shipping (ABS), on 11/DEC/2008 the manufacturer of the below listed product held a valid Manufacturing Assessment (MA) and a valid Product Design Assessment (PDA) for the below listed product, entitling the product to type approval.

The validity of the Manufacturing Assessment is dependent on satisfactory audits as required by the Rules.

The Product Design Assessment is valid only for products intended for use on ABS classed vessels, MODUs or facilities which are in existence or under contract for construction on the date of the ABS Rules used to evaluate the Product. For Date of ABS Rules used for evaluation; Please refer to the ABS Rules below. ABS makes no representations regarding type approval of the Product for use on vessels, MODUs or facilities built after the date of the ABS Rules used for evaluation.

Due to wide variety of specifications used in the products ABS has evaluated for Type Approval, it is part of our contract that; whether the standard is an ABS Rule or a non-ABS Rule, the Client has full responsibility for continued compliance with the standard.

PRYSMIAN CABLES Y SISTEMAS, S.L.
Model Name(s): AFUMEX NAU XTCUA 0.6/1kV

Presented to:

PRYSMIAN CABLES Y SISTEMAS, S.L.
CARRETERA C-15 KM 2
POLIGONO MASIA D EN NOTARI-PIRELLI
VILANOVA I LA GELTRU (BARCELONA)
08800
Spain

Intended Service:	Power control and lighting cable for fixed installations onboard ships and offshore units.
Description:	Armoured flame retardant, low smoke, halogen free, shipboard power, control and lighting cable with XLPE insulation and SHF1 sheath.
Ratings:	0.6/1.0kV, Maximum conductor operating temperature 90C
Service Restrictions:	Unit Certification is not required for this product.
Comments:	Records of test are to be maintained and submitted upon request.
Notes / Documentation:	This Product Design Assessment (PDA) is valid only for products intended for use on ABS classed vessels, MODUs or facilities which are in existence or under contract for construction on the date of the ABS Rules used to evaluate the Product.
Term of Validity:	This Design Assessment Certificate number 08-LD370005B-PDA, dated 18/Sep/2008 will expire on 17/Sep/2013 or at an earlier date should there be alterations to the product's design or changes to the referenced ABS Rules and other specifications, which affect the product. Product use on or after 1 January 2009, will be subject to compliance with the ABS Rules or specifications in effect when the vessel, MODU or facility is contracted. The product's acceptability on board ABS-classed vessels or facilities is defined in the service restrictions of this certificate.

ABS Rules: Steel Vessel Rules 2008 1-1-4/7.7, 4-8-3/9 and MODU Rules 2008 4-3-4/13


National Standards:

International Standards: IEC 60092-353, IEC 60332-1, IEC 60332-3-22, IEC 60331-21, IEC 60754-1, IEC 61034-2

Government Authority:

EUMED:

Others:



ABS Programs

ABS has used due diligence in the preparation of this certificate and it represents the information on the product in the ABS Records as of the date and time the certificate was printed. Type Approval requires Drawing Assessment, Prototype Testing and assessment of the manufacturer's quality assurance and quality control arrangements. Limited circumstances may allow only Prototype Testing to satisfy Type Approval. The approvals of Drawings and Products remain valid as long as the ABS Rule, to which they were assessed, remains valid. ABS cautions manufacturers to review and maintain compliance with all other specifications to which the product may have been assessed. Further, unless it is specifically indicated in the description of the product; Type Approval does not necessarily waive witnessed inspection or survey procedures (where otherwise required) for products to be used in a vessel, MODU or facility intended to be ABS classed or that is presently in class with ABS. Questions regarding the validity of ABS Rules or the need for supplemental testing or inspection of such products should, in all cases, be addressed to ABS.